

PRESENTED BY



**AN ISO/IEC 17025:2017
ACCREDITED CALIBRATION COMPANY**

DALLAS FT WORTH AUSTIN HOUSTON

NICOLSCALES.COM

800.225.8181

[CONTACT US](#)

NICOL SCALES & MEASUREMENT IS AN ISO ACCREDITED CALIBRATION COMPANY THAT HAS PROVIDED CALIBRATION, REPAIR AND SALES OF ALL TYPES OF WEIGHING AND MEASUREMENT PRODUCTS SINCE 1931.

380 Synergy

DIGITAL WEIGHT INDICATOR



RICE LAKE®
WEIGHING SYSTEMS

800-472-6703

www.ricelake.com

380 Synergy

DIGITAL WEIGHT INDICATOR



Utilize the 380 Synergy Series indicator for straightforward weighing systems including portable warehouse scales, material handling applications and more. The 380 can easily mount almost anywhere, making weight data visible exactly where you need it.

Durable Construction

A stainless steel, IP66 enclosure means the 380 Synergy is dust-tight and can stand up to high-pressure water. A bright, six-digit LCD display makes weight data easy to see.

Powerful, Straightforward Operation

The 380 Synergy is battery powered, providing up to 100 hours of continuous use. A five-button keypad makes operation quick and simple while RS-232 and USB ports make it easy to connect to peripheral equipment.

Configurable print formats allow you to print only the most important information to your application. Optional date/time and external power supply are also available to meet the needs of your application.

STANDARD FEATURES

- LCD display, six-digits 1 in (25 mm) tall
- Alkaline battery powered; requires 4 C-cell batteries (not included)
- Push button and keyed tare
- Two communication ports, RS-232 (three-wire), USB 2.0
- Five tactile buttons
- Configurable print formats
- 304 stainless steel, IP66 rated enclosure

OPTIONAL

- Time/date
- External power supply

SPECIFICATIONS

POWER:	Batteries: 4 Alkaline C-cell Optional: 115/230VAC to 12VDC adapter
POWER CONSUMPTION:	6 W max with optional external power adapter
BATTERY LIFE:	100 hours on Alkaline batteries with one 350Ω load cell, no backlight 45 hours on Alkaline batteries with four 350Ω load cells, low backlight 20 hours on Alkaline batteries with eight 350Ω load cells, low backlight
EXCITATION VOLTAGE:	5 VDC, 8 x 350Ω or 16 x 700Ω load cells
ANALOG SIGNAL INPUT RANGE:	-0.3 mV to +30 mV Common Mode Voltage 0.7V to 3.3V
ANALOG SIGNAL SENSITIVITY:	1 μV/graduation recommended
A/D SAMPLE RATE:	5, 6, 10, 12, 20, 25, 40, 50, 80, 100 Hz, software selectable
RESOLUTION:	Internal: 8,000,000 counts Display: 100,000
SYSTEM LINEARITY:	Within 0.01% full scale
COMMUNICATION PORTS:	One RS-232 (three-wire) One USB 2.0
STATUS ANNUNCIATORS:	g, lb, t, tn, kg, oz, battery level, PT, LT, gross, zero, unstable, net
DISPLAY:	Six 1 in (25 mm) tall, LCD digits
KEYS/BUTTONS:	5 tactile buttons
TEMPERATURE RANGE:	Legal: 14°F to 104°F (-10°C to 40°C) Industrial: 14°F to 122°F (-10°C to 50°C)
DIMENSIONS (W X H X D):	11.58 in x 8.57 in x 4.05 in (30 cm x 22 cm x 10 cm)
WEIGHT:	6.25 lb (3 kg)
RATING/MATERIAL:	Enclosure: IP66, 304 Stainless steel
EMC IMMUNITY:	10 v/M
WARRANTY:	Two-year limited warranty

APPROVALS



CC 21-051,
Class III/II/L,
10,000 d



AM-6184



LISTED

SALES AND TECHNICAL ASSISTANCE

RICE LAKE®
WEIGHING SYSTEMS

HEADQUARTERS

230 West Coleman Street
Rice Lake, Wisconsin 54868 - USA
Tel: (715) 234 9171 | Fax: (715) 234 6967
www.ricelake.com